Data sheet R927888

C1F-15U 540x450 FGD WM IN Cabinet

DESCRIPTION

Wall enclosure with front glass door, side and rear blind panels, 19" front uprights and assembled package
Economic, versatile, robustness and reliability. Quickly removable door and panels. Easily reversible door, Door opening 235°. Compatible with all 19" accessories.

SCOPE OF SUPPLY

- Disassemblable body.
- Rear body component includes a 19" module.
- Adjustable depth of front 19" uprights.
- Grounding wirings for panels supplied.
- Removable side panels.
- Removable and reversible front door.
- Fastening preparation for fans.

FEATURES

- Made with 1mm thick steel sheet.
- Uprights have a thickness of 2 mm.
- Position of the front 19" uprights are adjustable in progressive way
- Rear pillars are fixed and are part of the reinforcing structure of the bottom plate.
- 4 quickly folding plates guarantee the passage of the cables through the base and the roof.
- The easily reversible door is made of 4 mm thick tempered safety glass in 1 mm steel frame. The opening angle is 235° with the mountedpanels and 260° with-out panels.
- Ventilation slots on the roof for mounting single fans or a group of two fans with or without thermostat.
- Includes grounding kit for panels.

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Amount of height units	15 U
Rack mounting version	19" wall mounted rack
Assembly	Disassemblable body
Lockable	Yes

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	540 mm x 667 mm x 450 mm / 21.26 in x 26.26 in x 17.717 in (W x H x D)

Color	black
Weight load	40 kg